

Kinematic and dynamic approaches in gait optimization for humanoid robot locomotion

Kazan Federal University, 420008, Kremlevskaya 18, Kazan, Russia

Abstract

© Springer International Publishing AG 2018. Humanoid robot related research keeps attracting many researchers nowadays because of a high potential of bipedal locomotion. While many researchers concentrate on a robot body movement due to its direct contribution to the robot dynamics, the optimality of a leg trajectory has not been studied in details yet. Our paper is targeted to decrease this obvious gap and deals with optimal trajectory planning for bipedal humanoid robot walking. The main attention is paid to maximization of locomotion speed while considering velocity, acceleration and power limitations of each joint. The kinematic and dynamic approaches are used to obtain a desired optimal trajectory. Obtained results provide higher robot performance comparing to commonly used trajectories for control bipedal robots.

http://dx.doi.org/10.1007/978-3-319-55011-4_15

Keywords

Bipedal walking, Humanoids, Optimal trajectory planning

References

- [1] Wright, J., Jordanov, I.: Intelligent approaches in locomotion - a review. J. Intell. Robot. Syst. 80, 255–277 (2014)
- [2] Sakagami, Y., Watanabe, R., Aoyama, C., Matsunaga, S., Higaki, N., Fujimura, K.: The intelligent ASIMO: System Overview and Integration. 2478–2483. IEEE, New York (2008)
- [3] Ogura, Y., Aikawa, H., Shimomura, K., Kondo, H., Morishima, A., Lim, H.-o., Takanishi, A.: Development of a New Humanoid Robot WABIAN-2. 76–81. IEEE, New York (2006)
- [4] Shamsuddin, S., Ismail, L.I., Yussof, H., Zahari, N.I., Bahari, S., Hashim, H., Jaffar, A.: Humanoid Robot NAO: Review of Control and Motion Exploration. pp. 511– 516. IEEE, New York (2011)
- [5] Feng, S., Whitman, E., Xinjilefu, X., Atkeson, C.G.: Optimization-based full body control for the DARPA robotics challenge. J. Field Robot. 32, 293–312 (2015)
- [6] Vukobratovic, M., Borovac, B.: Zero-moment point - thirty five years of its life. Int. J. Hum. Robot. 01, 157–173 (2004)
- [7] Shafii, N., Abdolmaleki, A., Lau, N., Reis, L.P.: Development of an Omnidirectional Walk Engine for Soccer Humanoid Robots (2015)
- [8] Albert, A., Gerth, W.: Analytic path planning algorithms for bipedal robots without a trunk. J. Intell. Robot. Syst. 36, 109–127 (2003)
- [9] Sato, T., Sakaino, S., Ohnishi, K.: Real-time walking trajectory generation method with three-mass models at constant body height for three-dimensional biped robots. IEEE Trans. Indust. Electron. 58, 376–383 (2011)
- [10] Ha, T., Choi, C.-H.: An effective trajectory generation method for bipedal walking. Robot. Autonom. Syst. 55, 795–810 (2007)
- [11] Erik Cuevas, D.Z.: Polynomial Trajectory Algorithm for a Biped Robot (2010)

- [12] Katoh, R., Mori, M.: Control method of biped locomotion giving asymptotic stability of trajectory. *Automatica* 20, 405-414 (1984)
- [13] Furusho, J., Masubuchi, M.: Control of a dynamical biped locomotion system for steady walking. *J. Dyn. Syst. Meas. Control* 108, 111-118 (1986)
- [14] Liu, C., Wang, D., Chen, Q.: Central pattern generator inspired control for adaptive walking of biped robots. *IEEE Trans. Syst. Man Cybern. Syst.* 43, 1206-1215 (2013)
- [15] Kajita, S., Kanehiro, F., Kaneko, K., Fujiwara, K., Harada, K., Yokoi, K., Hirukawa, H.: Biped walking pattern generation by using preview control of zero-moment point. In: *Proceedings of the IEEE International Conference on Robotics and Automation, 2003. ICRA '03*, vol. 1622, pp. 1620-1626 (2003)
- [16] Katayama, T., Ohki, T., Inoue, T., Kato, T.: Design of an optimal controller for a discrete-time system subject to previewable demand. *Int. J. Control* 41, 677-699 (1985)
- [17] Goswami, A.: Postural stability of biped robots and the foot-rotation indicator (FRI) point. *Int. J. Robot. Res.* 18, 523-533 (1999)
- [18] Dau, V.-H., Chew, C.-M., Poo, A.-N.: Achieving energy-efficient bipedal walking trajectory through GA-based optimization of key parameters. *Int. J. Hum. Robot.* 6, 609-629 (2009)
- [19] Liu, Z., Wang, L., Chen, C.L.P., Zeng, X., Zhang, Y., Wang, Y.: Energy-efficiency-based gait control system architecture and algorithm for biped robots. *IEEE Trans. Syst. Man. Cybern. Part C (Appl. Rev.)* 42, 926-933 (2012)
- [20] Khusainov, R., Klimchik, A., Magid, E.: Swing leg trajectory optimization for a humanoid robot locomotion. In: *2016 13th International Conference on Informatics in Control, Automation and Robotics (ICINCO)* (2016)
- [21] Khusainov, R., Shimchik, I., Afanasyev, I., Magid, E.: Toward a human-like locomotion: modelling dynamically stable locomotion of an anthropomorphic robot in simulink environment. In: *2015 12th International Conference on Informatics in Control, Automation and Robotics (ICINCO)*, pp. 141-148 (2015)
- [22] Nakamura, M.: Trajectory planning for a leg swing during human walking. *IEEE Int. Conf. Syst. Man Cybern.* 1, 784-790 (2004)
- [23] Khusainov, R., Sagitov, A., Afanasyev, I., Magid, E.: Bipedal robot locomotion modelling with virtual height inverted pendulum in Matlab-Simulink and ROS-Gazebo environments. *J. Robot. Netw. Artif. Life* 3 (2016)
- [24] Tangpattanakul, P., Artrit, P.: Minimum-time trajectory of robot manipulator using Harmony Search algorithm. In: *6th International Conference on Electrical Engineering/Electronics, Computer, Telecommunications and Information Technology, 2009. ECTI-CON 2009*, pp. 354-357 (2009)
- [25] Si, J., Yang, L., Chao, L., Jian, S., Shengwei, M.: Approximate dynamic programming for continuous state and control problems. In: *17th Mediterranean Conference on Control and Automation, 2009. MED '09*, pp. 1415-1420 (2012)
- [26] Khusainov, R., Afanasyev, I., Magid, E.: Anthropomorphic robot modelling with virtual height inverted pendulum approach in Simulink: step length and period influence on walking stability. In: *The 2016 International Conference on Artificial Life and Robotics (ICAROB 2016)*, Japan (2016)
- [27] Klimchik, A., Pashkevich, A., Caro, S., Chablat, D.: Stiffness matrix of manipulators with passive joints: computational aspects. *IEEE Trans. Robot.* 28, 955-958 (2012)
- [28] Klimchik, A., Chablat, D., Pashkevich, A.: Stiffness modeling for perfect and non-perfect parallel manipulators under internal and external loadings. *Mech. Mach. Theory* 79, 1-28 (2014)
- [29] Klimchik, A., Pashkevich, A., Chablat, D., Hovland, G.: Compliance error compensation technique for parallel robots composed of non-perfect serial chains. *Robot. Comput. Integr. Manufact.* 29, 385-393 (2013)
- [30] Klimchik, A., Bondarenko, D., Pashkevich, A., Briot, S., Furet, B.: Compliance Error Compensation in Robotic-Based Milling. In: *Ferrier, J.-L., Bernard, A., Gusikhin, O., Madani, K. (eds.) Informatics in Control, Automation and Robotics: 9th International Conference, ICINCO 2012 Rome, Italy, July 28-31, 2012 Revised Selected Papers*, pp. 197-216. Springer International Publishing, Cham (2014)
- [31] Klimchik, A., Furet, B., Caro, S., Pashkevich, A.: Identification of the manipulator stiffness model parameters in industrial environment. *Mech. Mach. Theory* 90, 1-22 (2015)
- [32] Majima, K., Miyazaki, T., Ohishi, K.: Dynamic gait control of biped robot based on kinematics and motion description in Cartesian space. *Electr. Eng. Jpn.* 129, 96-104 (1999)
- [33] Mitobe, K., Capi, G., Nasu, Y.: Control of walking robots based on manipulation of the zero moment point. *Robotica* 18, 651-657 (2000)
- [34] Ude, A., Atkeson, C.G., Riley, M.: Programming full-body movements for humanoid robots by observation. *Robot. Autonom. Syst.* 47, 93-108 (2004)
- [35] Yamaguchi, J., Soga, E., Inoue, S., Takanishi, A.: Development of a bipedal humanoid robot-control method of whole body cooperative dynamic biped walking. In: *1999 IEEE International Conference on Robotics and Automation, 1999. Proceedings*, vol. 361, pp. 368-374 (1999)